

ADCOCHEM 225

Solvent-based, penetrating wood protection and release agent

ADCO
Construction-
and Mining
Chemicals

adcon
www.adcon-namibia.com

adcon cc
established 1994

Head Office : Nr 7 Eider Street, Lafrenz, PO Box 80490, Windhoek, Namibia Tel : +(264)61-215340 Fax : +(264)61-238429 E-mail : adcon@iafrica.com.na
Walvis Bay Branch: Unit 14, 10th Street, Factory Park, PO Box 4587, Walvis Bay, Namibia Tel : +(264)64-221343 Fax : +(264)64-221344 E-mail : wvb1@adcon.com.na

technical data sheet technical data sheet technical data sheet

DESCRIPTION

ADCOchem 225 is a low-viscosity, one-component ready-to-use solvent-based petroleum resin specifically formulated for the block and brick industry as a preservative treatment to the wooden pallets. The surface characteristics of ADCOchem 225 promote release of product from the pallet surface. ADCOchem 225 renders superior penetrating properties into the wood, thereby extending the service cycle of the pallet in production before requiring re-treatment.

APPLICATION

Clean the wooden surface well by wire brush to remove dirt and contamination. Ensure the pallet to be dry and apply ADCOchem 225 by brush or spray. The coverage varies according to the porosity of the wood; 10 – 15 m² per litre is an indicative industry average.

PHYSICAL PROPERTIES

Appearance clear / amber liquid
Specific gravity ±0.8

SAFETY

Contact with the skin should be avoided by wearing gloves, eye protection and protective clothing. In case of eye contact, wash well with water and obtain medical advice. Use only in well-ventilated areas.
Remember : Keep away from children, handle responsibly and consider the environment.

UPDATE

May 2017.

This supercedes all previous documentation.

